



DEGA NS II LCD

GAS DETECTION TRANSMITTER

- Detection types: catalytic, electrochemical, infrared, photoionization (PID)
- Detection of toxic and combustible gases and oxygen
- For explosive environments ATEX zone 2.
- Protection level IP54/ IP66 (with protection cover)
- Q Produced in compliance with standard SIL
- Q Output: 4-20mA, RS485, Modbus



ISO 9001:2015
Quality management Systems
Système de Qualité
www.sgs.com



Gas detection transmitter **DEGA NS II LCD**

DEGA NS II LCD transmitter is a part of the gas detection system. Transmitter is located in monitored premises in which critical situations due to accumulation of flammable or toxic substances can occur. The transmitter has an LCD display to show measured concentrations of detected substances in real time. The transmitter can be connected to control panels DEGA UPA III, DEGA UKA III and DEGA UDA III. Standard Output : RS485, without cable gland.

TECHNICAL SPECIFICATION:

Power supply:	8-30 V DC
Output:	4 - 20 mA, RS485, Modbus
Case protection level:	IP 54, with water protection cover DEGA WATER CAP IP66
Input:	3,7 W
Specification in compliance with ATEX:	II 3 G Ex db ic ec nC IIC T5/4 Gc Tamb: 0°C- +40°C
Placement:	BE3N2 - areas with danger of explosion, zone 22
Dimensions(WxHxD):	140 x 140 x 70 mm
Weight:	0,7 kg
Sensor technology:	catalytic, electrochemical, infrared, photoionization
Estimated life of sensor in clean environment:	catalytic (1-2 years),electrochemical (1-3 years), infrared (minimum 5 years), photoionization (5000 hours), semiconductor (1-2 years)
Relative humidity of the ambient air:	max. 95%

EXPANSION MODULES:

DEGA NS II LCD RS485

MODBUS, Internal module in transmitter

DEGA NS II LCD Relay Modul

Internal 3-relay, 250 V/10 A

Detected substance	Formula	Range	Sensor	Product type
Flammable and combustible gases	LEL	0-100 % LEL	CL	DEGA NSHC-CL 100 II LCD
Flammable and combustible gases	LEL	0-100 % LEL	IL	DEGA NSHC-IL 100 II LCD
VOC	C3H6O	0-5000 ppm	PID	DEGA NSVOC-PID II LCD
Ammonia	NH3	0-100 ppm	EL	DEGA NSA-EL 100 II LCD
Ammonia	NH3	0-1000 ppm	EL	DEGA NSA-EL 1000 II LCD
Gasoline vapor	C6H14	0-100 % LEL	CL	DEGA NSB-CL 100II LCD
Hydrogen bromide	HBr	0-20 ppm	EL	DEGA NSHBr-EL 20 II LCD
Butane	C4H10	0-100 % LEL	CL	DEGA NSP-CL 100 II LCD
Butane	C4H10	0-100 % LEL	IL	DEGA NSP-IL 100 II LCD
Butane	C4H10	0-5000 ppm	PID	DEGA NSP-PID II LCD
Ethanol	C2H6O	0-100 % LEL	IL	DEGA NSC2H5OH-IL 100 II LCD
Ethanol	C2H6O	0-450 ppm	PID	DEGA NSC2H5OH-PID 450 II LCD
Ethene	C2H4	0-100 % LEL	IL	DEGA NSC2H4-IL 100 II LCD
Ethylenoxid	C2H4O	0-10 ppm	EL	DEGA NSC2H4O-EL 10 II LCD
Ethylenoxid	C2H4O	0-100 % LEL	IL	DEGA NSC2H4O-IL 100 II LCD
Ethene	C2H4	0-10 ppm	EL	DEGA NSC2H4-EL 10 II LCD
Formaldehyde	CH2O	0-10 ppm	EL	DEGA NSCH2O-EL 10 II LCD
Phospine	PH3	0-5 ppm	EL	DEGA NSPH3-EL 5 II LCD
Hexane	C6H14	0-100 % LEL	IL	DEGA NSC6H14-IL 100 II LCD
Chlorine	Cl2	0-20 ppm	EL	DEGA NSCL2-EL 20 II LCD
Hydrogen chloride	HCl	0-20 ppm	EL	DEGA NSHCL-EL 20 II LCD
Hydrogen chloride	HCN	0-50 ppm	EL	DEGA NSHCN-EL 50 II LCD
Oxygen	O2	0-100 % LEL	EL	DEGA NSO2-EL 100 II LCD
Methane	CH4	0-100 % LEL	CL	DEGA NSM-CL 100 II LCD

Detected substance	Formula	Range	Sensor	Product type
Methane	CH4	0-100 % LEL	IL	DEGA NSM-IL 100 II LCD
Nitrogen dioxide	NO2	0-20 ppm	EL	DEGA NSNO2-EL 20 II LCD
Nitric oxide	NO	0-250 ppm	EL	DEGA NSNO-EL 250 II LCD
Nitrous oxide	N2O	0-1 % LEL	IL	DEGA NSN2O-IL 1 II LCD
Chlorine dioxide	ClO2	0-5 ppm	EL	DEGA NSCLO2-EL 5 II LCD
Sulfur dioxide	SO2	0-20 ppm	EL	DEGA NSSO2-EL 20 II LCD
Carbon monoxide	CO	0-1000ppm	EL	DEGA NSCO-EL 1000 II LCD
Carbon dioxide	CO2	0-5 % vol.	IL	DEGA NSCO2-IL 5 II LCD
Ozone	O3	0-5 ppm	EL	DEGA NSO3-EL 5 II LCD
Pentane	C5H12	0-100 % LEL	IL	DEGA NSC5H12-IL 100 II LCD
Hydrogen peroxide	H2O2	0-100 ppm	EL	DEGA NSH2O2-EL 100 II LCD
Propylene	C3H6	0-100 % LEL	IL	DEGA NSC3H6-IL 100 II LCD
Silane	SiH4	0-50 ppm	EL	DEGA NSSiH4-EL 50 II LCD
Hydrogen sulfide	H2S	0-50 ppm	EL	DEGA NSH2S-EL 50 II LCD
Hydrogen sulfide	H2S	0-2000 ppm	EL	DEGA NSH2S-EL 2000 II LCD
Hydrogen	H2	0-1000 ppm	EL	DEGA NSH-EL 1000 II LCD
Hydrogen	H2	0-100 % LEL	CL	DEGA NSH-CL 100 II LCD
Hydrogen	H2	0-4000 ppm	EL	DEGA NSH-EL 4000 II LCD
Other toxic gases	-	According gas type	EL	More than 50 other gases
Other combustible gases	-	According gas type	IL	More than 50 other gases
Other combustible gases	-	According gas type	CL	More than 50 other gases



Transmitter is designed for detection in industrial and commercial environments requiring certification ATEX (Zone 2).

AVAILABLE ACCESSORIES:



Cover for transmitter NS II LCD - mechanical




Cover for transmitter NS II LCD - Stainless steel 316



DEGA GAS INLET NS II LCD calibration adapter (cup)



DEGA WATER CAP Splash cap, NS II LCD



Sensor DEGA NS II LCD

Manufacturer: DEGA CZ s.r.o., Malešická 2850/22c, Czech Republic | e-mail: export@dega.co.com, web: www.dega.co.com

© 2020 DEGA CZ s.r.o. all rights reserved